

# INSTARMAC

## SAFETY DATA SHEET PT CABLE GROUT 20

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name PT CABLE GROUT 20

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer Instarmac Group plc  
Danny Morson Way  
Birch Coppice Business Park  
Dordon, Tamworth  
Staffordshire. B78 1SE  
United Kingdom  
Tel: +44 (0) 1827 254400  
Fax: +44 (0) 1827 285386  
email@instarmac.co.uk www.instarmac.co.uk

#### 1.4. Emergency telephone number

Emergency telephone +44 (0)7971 217 347 (24 hours)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (SI 2019 No. 720)

Physical hazards Not Classified  
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335  
Environmental hazards Not Classified

#### 2.2. Label elements

##### Hazard pictograms



Signal word Danger

Hazard statements  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.

## PT CABLE GROUT 20

<b>Precautionary statements</b>	<p>P261 Avoid breathing dust.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

**Contains** Cement

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.1. Substances

Classification according to EC  
1272/2008 (CLP)

##### 3.2. Mixtures

<b>Cement</b>	<b>60-100%</b>
CAS number: 65997-15-1	EC number: 266-043-4
<b>Classification</b> Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1B - H317 STOT SE 3 - H335	
<b>Cement</b>	<b>1-5%</b>
CAS number: 65997-16-2	EC number: 266-045-5
<b>Classification</b> Not Classified	

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>General information</b>	Get medical advice/attention if you feel unwell.
<b>Inhalation</b>	If exposed to excessive levels of dust or fumes, remove to fresher air, get medical attention if symptoms develop.
<b>Ingestion</b>	If swallowed, seek medical advice immediately and show this container or label.

## PT CABLE GROUT 20

**Skin contact** Get medical attention if irritation persists after washing.

**Eye contact** Get medical attention immediately. Continue to rinse.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for firefighters

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

### 6.4. Reference to other sections

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.3. Specific end use(s)

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### **Cement**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

##### **Cement**

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

#### Cement (CAS: 65997-15-1)

##### **DNEL**

A derived no-effect level (DNEL) of 1 mg/m<sup>3</sup> (as respirable dust) over an hour shift has been set.

### 8.2. Exposure controls

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

### 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

## PT CABLE GROUT 20

### SECTION 12: Ecological information

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

### SECTION 14: Transport information

#### 14.1. UN number

#### 14.2. UN proper shipping name

#### 14.3. Transport hazard class(es)

#### 14.4. Packing group

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical safety assessment

### SECTION 16: Other information

Revision date	10/11/2022
Revision	2
Supersedes date	09/11/2022
SDS number	20635
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

0